2.3. HEAVY LINE
2.3.1. NZO600H

DESCRIPTION

telescopic loading spout for dust-free loading of dry, dusty bulk solids on trucks and railcars

OPERATION QUALITIES

- max. flow rate 500 m³/h
- particle size 0-100 mm
- inlet diameter DN600
- pipe for connection to external filtration
- operating temperature -20 °C / +80 °C
- motor drive 2.2 kW
- loading conduit consisting of internal telescopic tubes and outer bellows

DESIGN

- electric winch with limit switches for highest and lowest position, emergency sensors for highest and lowest positions
- terminal box for cable connection
- level switch – 2x rotary
- dustproof bell with rubber skirt at the lower end of the loading spout

ADDITIONAL ACCESSORIES

- electric control box
- shut off valves (manual, electro, pneumatic)
- design for ATEX / non-standard temperature (-40 °C / +250 °C)

L_{min} (rectracted lenght)	L_{max} (extracted lenght)	Travel (H)	Weight
1940	3635	1695	631
1900	4670	2770	949
2160	4729	2569	704
2160	5060	2900	798
2230	5151	2921	750
2490	6150	3660	823
2600	6700	4100	906
2650	7200	4550	1100
2700	7700	5000	1125
2800	8200	5400	1170



0 - 100

max. 500 m³/h

Robust-design telescopic loading spout type NZO600H with the dustproof bell, rubber skirt and level indicator guarantees you a dustless loading of dry, dusty bulk solids on trucks or railway cars.

2.3. HEAVY LINE
2.3.1. NZO600H

