



V-пръстен, форма VS

V-пръстен Озн.	Монтажен канал				Размери на V-пръстен			
	Вал-Ø d ₁	d ₂ max.	d ₃ min	b ₁	d	s	a	b
VS-5	4,5 – 5,5	d ₁ +1	d ₁ +6	4,5±0,4	4	2	3,9	5,2
VS-6	5,5 – 6,5	↑	↑	↑	5	↑	↑	↑
VS-7	6,5 – 8,0	↓	↓	↓	6	↓	↓	↓
VS-8	8,0 – 9,5	d ₁ +1	d ₁ +6	4,5±0,4	7	2	3,9	5,2
VS-10	9,5 – 11,5	d ₁ +2	d ₁ +9	6,7±0,6	9	3	5,6	7,7
VS-12	11,5 – 13,5	↑	↑	↑	10,5	↑	↑	↑
VS-14	13,5 – 15,5	↓	↓	↓	12,5	↓	↓	↓
VS-16	15,5 – 17,5	↑	↑	↑	14	↑	↑	↑
VS-18	17,5 – 19,0	↓	d ₁ +9	6,7±0,6	16	3	5,6	7,7
VS-20	19 – 21	↑	d ₁ +12	9,0±0,8	18	4	7,9	10,5
VS-22	21 – 24	↓	↑	↑	20	↑	↑	↑
VS-25	24 – 27	d ₁ +2	↑	↑	22	↑	↑	↑
VS-28	27 – 29	d ₁ +3	↑	↑	25	↑	↑	↑
VS-30	29 – 31	↑	↑	↑	27	↑	↑	↑
VS-32	31 – 33	↑	↓	↓	29	↓	↓	↓
VS-35	33 – 36	↑	↑	↑	31	↑	↑	↑
VS-38	36 – 38	↑	d ₁ +12	9,0±0,8	34	4	7,9	10,5
VS-40	38 – 43	↑	d ₁ +15	11,0±1,0	36	5	9,5	13,0
VS-45	43 – 48	↑	↑	↑	40	↑	↑	↑
VS-50	48 – 53	↑	↑	↑	45	↑	↑	↑
VS-55	53 – 58	↑	↑	↑	49	↑	↑	↑
VS-60	58 – 63	↑	↓	↓	54	↓	↓	↓
VS-65	63 – 68	d ₁ +3	d ₁ +15	11,0±1,0	58	5	9,5	13,0
VS-70	68 – 73	d ₁ +4	d ₁ +18	13,5±1,2	63	6	11,3	15,5
VS-75	73 – 78	↑	↑	↑	67	↑	↑	↑
VS-80	78 – 83	↑	↑	↑	72	↑	↑	↑
VS-85	83 – 88	↑	↑	↑	76	↑	↑	↑
VS-90	88 – 93	↑	↓	↓	81	↓	↓	↓
VS-95	93 – 98	↑	↑	↑	85	↑	↑	↑
VS-100	98 – 105	↑	d ₁ +18	13,5±1,2	90	6	11,3	15,5
VS-110	105 – 115	↑	d ₁ +21	15,5±1,5	99	7	13,1	18,0
VS-120	115 – 125	↑	↑	↑	108	↑	↑	↑
VS-130	125 – 135	↑	↑	↑	117	↑	↑	↑
VS-140	135 – 145	↓	↓	↓	126	↓	↓	↓
VS-150	145 – 155	d ₁ +4	d ₁ +21	15,5±1,5	135	7	13,1	18,0
VS-160	155 – 165	d ₁ +5	d ₁ +24	18,0±1,8	144	8	15,0	20,5
VS-170	165 – 175	↑	↑	↑	153	↑	↑	↑
VS-180	175 – 185	↑	↑	↑	162	↑	↑	↑
VS-190	185 – 195	↓	↓	↓	171	↓	↓	↓
VS-199	195 – 210	d ₁ +5	d ₁ +24	18,0±1,8	180	8	15,0	20,5

Форма VS

Стандартни размери с наклонен гръб и усилена основа.
Наличности на склад.

